



# TOP'GS

Standard NF-T-30608



## ➤ GENERAL INFORMATION

- Spray-on filler
- Smooths concrete and pre-cast slabs
- Smooths plasterboard
- Renovates glass wool coverings
- White, smooth, fine finish
- Odourless

## ➤ RECOMMENDED USES

- Smoothing shuttered concrete, pre-cast slabs, skimming aerated concrete, plasterboard and renovation of glass wool coverings.
- Wood surfaces primed with solvent primer
- Surfaces must be clean, dry and sound (6 - 16% humidity).

### ➤ Advantages

- Enables direct application of paint

## ➤ APPLICATION

- Use in accordance with applicable French DTU recommendations and above 5°C.
- Use with all paste product machines, easily smoothed in one or two coats, depending on the state of the surface and desired finish.
- Clean all equipment with water

➤ **COVERAGE:** 1 - 2.5 kg/m<sup>2</sup> per coat

➤ **DRYING TIME:** From 5 to 12 hours depending on the conditions and thickness

➤ **PACKAGING:** 25 kg bag

➤ **SHELF LIFE:** 18 months in unopened container. Keep from freezing.

Composition	
Thinners:	Water
Extenders:	Calcium Carbonates, Silica
Additives:	Dispersant, Bactericide, Fungicide
Thickeners:	Cellulosic agents, polyacrylates, clay
Binders:	Acrylic Dispersant
Density:	1.88
Solid content:	75.00%
VOC content:	< 1g/l